1

Docket No. AUS9-2000-0692-US1

# METHOD AND APPARATUS FOR USING A PRINTING SYSTEM TO
# TRANSMIT DATA TO A SERVER
## BACKGROUND OF THE INVENTION

5    **1. Technical Field:**

The present invention relates generally to an
improved data processing system, and in particular to a
method and apparatus for transferring data.  Still more
particularly, the present invention provides a method and
10   apparatus for transmitting legacy data to a destination.

**2. Description of Related Art:**

15       The Internet, also referred to as an "internetwork",
is a set of computer networks, possibly dissimilar,
joined together by means of gateways that handle data
transfer and the conversion of messages from the sending
network to the protocols used by the receiving network
20   (with packets if necessary).  When capitalized, the term
"Internet" refers to the collection of networks and
gateways that use the TCP/IP suite of protocols.

The Internet has become a cultural fixture as a
source of both information and entertainment.  Many
25   businesses are creating Internet sites as an integral
part of their marketing efforts, informing consumers of
the products or services offered by the business or
providing other information seeking to engender brand
loyalty.  Many federal, state, and local government
30   agencies are also employing Internet sites for
informational purposes, particularly agencies which must

interact with virtually all segments of society such as the Internal Revenue Service and secretaries of state. Providing informational guides and/or searchable databases of online public records may reduce operating

5   costs.  Further, the Internet is becoming increasingly popular as a medium for commercial transactions.

Currently, the most commonly employed method of transferring data over the Internet is to employ the World Wide Web environment, also called simply "the Web".

10  Other Internet resources exist for transferring information, such as File Transfer Protocol (FTP) and Gopher, but have not achieved the popularity of the Web. In the Web environment, servers and clients effect data transaction using the Hypertext Transfer Protocol (HTTP),

15  a known protocol for handling the transfer of various data files (e.g., text, still graphic images, audio, motion video, etc.).  The information in various data files is  formatted for presentation to a user by a standard page description language, the Hypertext Markup

20  Language (HTML).  In addition to basic presentation formatting, HTML allows developers to specify "links" to other Web resources identified by a Uniform Resource Locator (URL).  A URL is a special syntax identifier defining a communications path to specific information.

25  Each logical block of information accessible to a client, called a "page" or a "Web page", is identified by a URL. The URL provides a universal, consistent method for finding and accessing this information, not necessarily for the user, but mostly for the user's Web "browser".  A

30  browser is a program capable of submitting a request for information identified by an identifier, such as, for example, a URL.  A user may enter a domain name through a

graphical user interface (GUI) for the browser to access a source of content. The domain name is automatically converted to the Internet Protocol (IP) address by a domain name system (DNS), which is a service that

5 translates the symbolic name entered by the user into an IP address by looking up the domain name in a database.

The Internet also is widely used to transfer applications to users using browsers. With respect to commerce on the Web, individual consumers and business

10 use the Web to purchase various goods and services. In offering goods and services, some companies offer goods and services solely on the Web while others use the Web to extend their reach.

Many businesses on the Internet use commercially

15 available packages, such as accounting packages. These packages are typically directed towards consumers and small businesses and do not provide easy access to data or an ability to transmit the data to other systems. As these businesses participate in business-to-business

20 transactions on the Internet, this deficiency places them at a disadvantage. For example, some suppliers or distributors offer discounts for electronic invoices. With the presently available commercial packages, generating an electronic invoice for a supplier requires

25 much effort because these packages do not provide an ability to transmit data to other non-compatible software systems. Presently, these businesses must use custom software specifically written to generate electronic invoices or generate them by hand.

30 Therefore, it would be advantageous to have an improved method and apparatus for transmitting data from these more limited consumer or small business grade

Docket No. AUS9-2000-0692-US1

programs to a destination such as a server.

Docket No. AUS9-2000-0692-US1

## SUMMARY OF THE INVENTION

5      The present invention provides a method and
apparatus in a data processing system for transferring
printer data. A printer data stream is received.  A
format is identified for the printer data stream in
response to receiving the printer data stream. Data is
10    extracted from the printer data stream to form extracted
data.  The extracted data is formatted into a format for
a specific destination to form formatted data.  The
formatted data is transmitted to the destination.

15

Docket No. AUS9-2000-0692-US1

## BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the
5  invention are set forth in the appended claims.  The
invention itself, however, as well as a preferred mode of
use, further objectives and advantages thereof, will best
be understood by reference to the following detailed
description of an illustrative embodiment when read in
10  conjunction with the accompanying drawings, wherein:

**Figure 1** is a pictorial representation of a network
of data processing systems in which the present invention
may be implemented;
15  **Figure 2** is a block diagram of a data processing
system that may be implemented as a server in accordance
with a preferred embodiment of the present invention;
**Figure 3** is a block diagram illustrating a data
processing system in accordance with a preferred
20  embodiment of the present invention;
**Figure 4** is a diagram illustrating components used
to transmit data from an application to a destination
using a printer driver subsystem in accordance with a
preferred embodiment of the present invention;
25  **Figure 5** is an illustration of an invoice processed
by the mechanism of the present invention in accordance
with a preferred embodiment of the present invention;
**Figure 6** illustrates a printer data stream from
which data is extracted by a data extraction object in
30  accordance with a preferred embodiment of the present
invention;

Docket No. AUS9-2000-0692-US1

**Figure 7** is an illustration of a pattern used for data extraction in accordance with a preferred embodiment of the present invention;

**Figure 8** is a graphical representation of a pattern
5   overlaying a printer stream in accordance with a preferred embodiment of the present invention;

**Figure 9** is an illustration of a data structure containing data extracted from a printer data stream in accordance with a preferred embodiment of the present
10   invention;

**Figure 10** is a flowchart of a process used for processing a printer data stream in accordance with a preferred embodiment of the present invention;

**Figure 11** is a flowchart of a process used for
15   extracting data in accordance with a preferred embodiment of the present invention; and

**Figure 12** is a flowchart of a process used for formatting and transmitting data in accordance with a preferred embodiment of the present invention.
20

Docket No. AUS9-2000-0692-US1

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, **Figure 1** depicts
5   a pictorial representation of a network of data
processing systems in which the present invention may be
implemented. Network data processing system **100** is a
network of computers in which the present invention may
be implemented.  Network data processing system **100**
10   contains a network **102**, which is the medium used to
provide communications links between various devices and
computers connected together within network data
processing system **100**. Network **102** may include
connections, such as wire, wireless communication links,
15   or fiber optic cables.

In the depicted example, a server **104** is connected
to network **102** along with storage unit **106**.  In addition,
clients **108, 110,** and **112** also are connected to network
**102**.  These clients **108, 110,** and **112** may be, for
20   example, personal computers or network computers.  In the
depicted example, server **104** provides data, such as boot
files, operating system images, and applications to
clients **108-112**.  Clients **108, 110,** and **112** are clients
to server **104**.  Network data processing system **100** may
25   include additional servers, clients, and other devices
not shown.  In the depicted example, network data
processing system **100** is the Internet with network **102**
representing a worldwide collection of networks and
gateways that use the TCP/IP suite of protocols to
30   communicate with one another.  At the heart of the
Internet is a backbone of high-speed data communication

Docket No. AUS9-2000-0692-US1

lines between major nodes or host computers, consisting
of thousands of commercial, government, educational and
other computer systems that route data and messages. Of
course, network data processing system 100 also may be

5   implemented as a number of different types of networks,
such as for example, an intranet, a local area network
(LAN), or a wide area network (WAN). Figure 1 is intended
as an example, and not as an architectural limitation for
the present invention.

10      Referring to Figure 2, a block diagram of a data
processing system that may be implemented as a server,
such as server 104 in Figure 1, is depicted in accordance
with a preferred embodiment of the present invention.
Data processing system 200 may be a symmetric

15  multiprocessor (SMP) system including a plurality of
processors 202 and 204 connected to system bus 206.
Alternatively, a single processor system may be employed.
Also connected to system bus 206 is memory
controller/cache 208, which provides an interface to

20  local memory 209. I/O bus bridge 210 is connected to
system bus 206 and provides an interface to I/O bus 212.
Memory controller/cache 208 and I/O bus bridge 210 may be
integrated as depicted.

        Peripheral component interconnect (PCI) bus bridge

25  214 connected to I/O bus 212 provides an interface to PCI
local bus 216. A number of modems may be connected to
PCI bus 216. Typical PCI bus implementations will
support four PCI expansion slots or add-in connectors.
Communications links to network computers 108-112 in

30  Figure 1 may be provided through modem 218 and network
adapter 220 connected to PCI local bus 216 through add-in

boards.

Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI buses **226** and **228**, from which additional modems or network adapters may be

5    supported.  In this manner, data processing system **200** allows connections to multiple network computers.  A memory-mapped graphics adapter **230** and hard disk **232** may also be connected to I/O bus **212** as depicted, either directly or indirectly.

10    Those of ordinary skill in the art will appreciate that the hardware depicted in **Figure 2** may vary.  For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted.  The depicted example

15    is not meant to imply architectural limitations with respect to the present invention.
The data processing system depicted in **Figure 2** may be, for example, an IBM RISC/System 6000 system, a product of International Business Machines Corporation in Armonk,

20    New York, running the Advanced Interactive Executive (AIX) operating system.

With reference now to **Figure 3**, a block diagram illustrating a data processing system is depicted in which the present invention may be implemented.  Data

25    processing system **300** is an example of a client computer. Data processing system **300** employs a peripheral component interconnect (PCI) local bus architecture.  Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and

30    Industry Standard Architecture (ISA) may be used.
Processor **302** and main memory **304** are connected to PCI

local bus **306** through PCI bridge **308**. PCI bridge **308** also may include an integrated memory controller and cache memory for processor **302**. Additional connections to PCI local bus **306** may be made through direct component

5 interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**,

10 graphics adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Small

15 computer system interface (SCSI) host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, and CD-ROM drive **330**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

20     An operating system runs on processor **302** and is used to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system, such as Windows 2000, which is

25 available from Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provide calls to the operating system from Java programs or applications executing on data processing system **300**. "Java" is a

30 trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented operating system,

Docket No. AUS9-2000-0692-US1

and applications or programs are located on storage
devices, such as hard disk drive **326**, and may be loaded
into main memory **304** for execution by processor **302**.
Those of ordinary skill in the art will appreciate that
5    the hardware in **Figure 3** may vary depending on the
implementation. Other internal hardware or peripheral
devices, such as flash ROM (or equivalent nonvolatile
memory) or optical disk drives and the like, may be used
in addition to or in place of the hardware depicted in
10   **Figure 3**. Also, the processes of the present invention
may be applied to a multiprocessor data processing
system.

      As another example, data processing system **300** may
be a stand-alone system configured to be bootable without
15   relying on some type of network communication interface,
whether or not data processing system **300** comprises some
type of network communication interface. As a further
example, data processing system **300** may be a Personal
Digital Assistant (PDA) device, which is configured with
20   ROM and/or flash ROM in order to provide non-volatile
memory for storing operating system files and/or
user-generated data.

      The depicted example in **Figure 3** and above-described
examples are not meant to imply architectural
25   limitations. For example, data processing system **300**
also may be a notebook computer or hand held computer in
addition to taking the form of a PDA. Data processing
system **300** also may be a kiosk or a Web appliance.
The present invention provides a method, apparatus, and
30   computer implemented instructions for using a printing
subsystem to transmit data to a server, such as server

**104** in **Figure 1**. Of course, the data transfer may be to any data processing system, such as from client **108** to client **110**, or from server **104** to client **112** or storage **106**. The mechanism of the present invention allows

5 information from an application to be sent to a printer driver system, which extracts the relevant data, formats the data, and transmits the data to a destination. In this manner, no changes are needed to the application and the formatting is provided through a printer driver

10 system.

Turning next to **Figure 4**, a diagram illustrating components used to transmit data from an application to a destination using a printer driver subsystem is depicted in accordance with a preferred embodiment of the present

15 invention. Printer driver subsystem **400** may be used in a data processing system, such as data processing system **200** or data processing system **300** to place data in an appropriate format for a destination.

In this example, printer driver subsystem **400**

20 includes a printer driver **402**, a data extraction object **404**, data processing objects **406-410**, and formats and patterns **412-416**. Printer driver subsystem receives a printer data stream **418** from application **420** and formats the data for use at data destination **422**. In this

25 example, application **420** may be a financial package, which does not provide an ability to export data in a format recognized by data destination **422**. For example, an electronic invoice may be generated by application **420**. According to the present invention, this invoice is

30 printed to generate a printer data stream **418**. This printer data stream is received by printer driver **402**,

Docket No. AUS9-2000-0692-US1

which examines printer data stream **418** to determine the data format of data within printer data stream **418**. A pattern is identified for use in data extraction by printer driver **402** from formats and patterns **412-416**.

5   Printer data stream **418** is passed on to data extraction object **404**, which uses the identified pattern to "scrape" or extract data from the printer data stream and prepare this data for processing.

   Thereafter, this extracted data is then passed to a
10  data processing object, such as data processing object **406, 408,** or **410**. The data processing object formats the extracted data and sends it to data destination **422**. Each data processing object may be configured to format data into a particular format for a particular destination.
15  For example, data processing object **406** may generate an extensible markup language (XML) document while data processing object **408** generates a hypertext markup language (HTML) document. Further, data processing object **406** may send the formatted data to one server, while data
20  processing object **408** sends the formatted data to another server. Data destination **422** make take various forms. For example, this destination may be a local database or a remote server. On a remote server, a database, an enterprise Java bean, a servlet, an applet, or a script
25  may be the target within the server. The data processing object may communicate with these programs or processes to transfer the formatted data.

   In this example, the electronic invoice generated by application **420** is processed by printer driver **402** to
30  identify the format of data within printer data stream **418**. A pattern is selected by printer driver **402** and

used by data extraction object **404** to extract the appropriate data from printer data stream **418**. The pattern defines the format in which the extracted data should be stored for use in generating the appropriate

5 output for the destination. The appropriate output is based on the format identified for printer data stream **418**. In other words, data for the invoice is parsed out from printer-specific or printer formatting information in printer data stream **418**. A data processing object,

10 such as data processing object **406**, formats the data into a form for use by data destination **422**. The format is identified by printer driver **402** based on information within printer data stream **418**. This format is the format that is to be used to send the data to data

15 destination **422**. For example, the data format may take a form of an extensible markup language (XML) document.

Turning next to **Figure 5**, an illustration of an invoice processed by the mechanism of the present invention is depicted in accordance with a preferred

20 embodiment of the present invention. Invoice **500** is an example of a document printed from a data stream sent to a printer, which would be generated by application **420** in **Figure 4**. In this example, data is sent to generate formatting, such as the rows and columns, as well as

25 different font types in invoice **500**. In this example, data found in fields **502-546** is identified by print driver **402** and extracted by data extraction object **404**. Based on the data found in different fields, printer driver **402** may identify a format and pattern for use by

30 data extraction object **404**.

Turning next to **Figure 6**, data structure **600**

Docket No. AUS9-2000-0692-US1

illustrates a pattern, which may be used to store data
when the data is extracted from printer data stream **418**
by data extraction object **404** in **Figure 4**. In this
example, printer data stream **600** stores the data in
5  various rows and columns for formatting by a data
processing object, such as data processing object **406**.

   With reference now to **Figure 7**, an illustration of a
pattern used for data extraction is depicted in
accordance with a preferred embodiment of the present
10  invention. Pattern **700** illustrates fields that will be
extracted when compared to data from a printer data
stream. Pattern **700** may be defined graphically by a user
highlighting fields in a graphical representation of a
printer data stream such as printer data stream **600** in
15  **Figure 6**. Alternatively, other mechanisms may be used to
implement or represent a pattern. For example, text
triplets, such as a line number, starting column, and
length, may be used.

   Turning next to **Figure 8**, a graphical representation
20  of a pattern overlaying a printer stream is depicted in
accordance with a preferred embodiment of the present
invention. In this example, invoice **800** contains fields
**802-836**, which illustrate data that is to be extracted
from an invoice such as that in printer data stream **600**
25  in **Figure 6** using pattern **700** in **Figure 7**.

   With reference now to **Figure 9**, an illustration of a
data structure containing data extracted from a printer
data stream is depicted in accordance with a preferred
embodiment of the present invention. Data structure **900**
30  contains data extracted from printer data stream **600** in
**Figure 6** using pattern **700** in **Figure 7**.

Docket No. AUS9-2000-0692-US1

With reference now to **Figure 10**, a flowchart of a process used for processing a printer data stream is depicted in accordance with a preferred embodiment of the present invention. The process shown in **Figure 10** may be
5    implemented in printer driver **402** in **Figure 4**.

The process begins by receiving a printer data stream from an application (step **1000**). The data format is identified (step **1002**). For example, the string in INVOICE found in field **546** in **Figure 5** may be used to
10   indicate that the target format is an electronic invoice. The identification of the customer in field **504** may be used to identify a preferred data interexchange format for the electronic invoice. Next, a pattern for data extractions is identified (step **1004**). The data may be
15   stored in various formats, such as row/column list pairs associated with specific data and possibly associated with a specific data type. An example data structure is data structure **700** in **Figure 7**. The format definition for this data may be stored in different forms, such as
20   extensible markup language (XML), text, or binary data. The identified format and pattern is sent to a data extraction object (step **1006**). This data extraction object is used to extract or "scrape" data from the printer data stream. The data extracted from the data
25   stream is stored using the pattern identified for the particular format.

With reference now to **Figure 11**, a flowchart of a process used for extracting data is depicted in accordance with a preferred embodiment of the present
30   invention. The process illustrated in **Figure 11** may be implemented in data extraction object **404** in **Figure 4**.

The process begins by receiving a data format and
pattern (step **1100**). This data format and pattern is
received from a print driver, such as print driver **402** in
**Figure 4**. The printer data stream is then received (step

5    **1102**). Data is extracted from the printer data stream
using the identified pattern (step **1104**). The extracted
data is prepared for processing (step **1106**). In this
step, the data extraction object uses the identified
pattern to place extracted data from the printer data

10   stream into specific locations and also may associate
this data with a label. The associated data is kept in a
collection with other associated data. This collection
may be located in a data structure, such as data
structure **900** in **Figure 9**. The data structure may take

15   various forms such as, for example, an XML document, a
hash table, and a binary record. If the extracted data
is stored in a binary format such as a hash table or
binary record, the extraction step performed by the data
extraction object also may convert the data into

20   non-textual types, such as integer or data, as
appropriate.

     The data is then sent to a data processing object
for formatting (step **1108**), with the process terminating
thereafter. In this example, the data extraction object

25   may send or select a particular data processing object
from a set of data processing objects to send the data to
a particular data destination.

     Turning next to **Figure 12**, a flowchart of a process
used for formatting and transmitting data is depicted in

30   accordance with a preferred embodiment of the present
invention. The process illustrated in **Figure 12** may be

Docket No. AUS9-2000-0692-US1

implemented in a data processing object, such as data
processing object **406** in **Figure 4**.

The process begins by receiving data from the data
extraction object (step **1200**). The data is then

5    formatted (step **1202**). This format is based on the
format identified by printer driver **402** in **Figure 4**. The
formatted data is then sent to the destination (step
**1204**), with the process terminating thereafter. The
formatting of data may differ depending on the particular

10   data processing object used. For example, one data
processing object may generate an XML document, while
another data processing object generates an HTML
document.

It is important to note that while the present

15   invention has been described in the context of a fully
functioning data processing system, those of ordinary
skill in the art will appreciate that the processes of
the present invention are capable of being distributed in
the form of a computer readable medium of instructions

20   and a variety of forms and that the present invention
applies equally regardless of the particular type of
signal bearing media actually used to carry out the
distribution. Examples of computer readable media
include recordable-type media, such as a floppy disk, a

25   hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and
transmission-type media, such as digital and analog
communications links, wired or wireless communications
links using transmission forms, such as, for example,
radio frequency and light wave transmissions. The

30   computer readable media may take the form of coded
formats that are decoded for actual use in a particular

Docket No. AUS9-2000-0692-US1

data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the

5 invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. For example, printer data driver **402** in **Figure 4** may exclude the step of examining the printer data stream to identify a data format and select a pattern for

10 data extraction. Instead, a particular printer driver may be configured for a particular data format. As a result, a user may select from different printer drivers for a particular data format. The embodiment was chosen and described in order to best explain the principles of

15 the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

20